



Impact of operational conditions and reactor configuration on process performance and microbial community in short solid retention time EBPR systems

Valverde Perez, Borja; Wágner, Dorottya Sarolta; Cecchin, Francesca; Jensen, Christian K.; Smets, Barth F.; Plósz, Benedek G.

Publication date:
2015

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Valverde Perez, B., Wágner, D. S., Cecchin, F., Jensen, C. K., Smets, B. F., & Plósz, B. G. (2015). *Impact of operational conditions and reactor configuration on process performance and microbial community in short solid retention time EBPR systems*. Poster session presented at 1st IWA Resource Recovery Conference, Ghent, Belgium.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Impact of operational conditions and reactor configuration on process performance and microbial community in short solid retention time EBPR systems

Borja Valverde-Pérez*, Dorottya S. Wágner, Francesca Cecchin, Christian K. Jensen, Barth F. Smets, Benedek Gy. Plósz

*bvape@env.dtu.dk Department of Environmental Engineering, Technical University of Denmark, Miljøvej, Building 113, 2800 Kgs. Lyngby, DENMARK

1. INTRODUCTION

Current research promotes resource recovery using different strategies:

- Energy recovery using A-stage systems [1]
- Phosphorus recovery using low SRT EBPR systems [2,3]
- To minimize ammonia oxidation, so it can assimilated by phototrophic organisms [2]
- Water reuse for “fertigation” [2-4]



Optimal N-to-P ratio



Fertigation

Common element:
short SRT EBPR systems



2. OBJECTIVES

- To assess the **start-up** operation of a short SRT EBPR system
- To **define** the **microbial community** affecting the performance of the short SRT EBPR system
- To **test** the process performance **stability** in two different **configurations**:
 - *Sequencing batch reactor (SBR)*
 - *Continuous flow system*

3. RESULTS

Sequencing Batch Reactor:


- Stable operation at SRT 8 days (day 50).
- Incomplete nitrification when the SRT was shifted to 5 days (data not shown)
- Filamentous bulking after nitrifiers were washed out at SRT=4 days
- qFISH revealed high abundance of *M. parvicella* (7%) and *Thiothrix* (17%) at relatively low DO levels in aerobic phase



Filamentous bulking starts


20 days after PAOs are washed out

Microbial community when the filamentous bulking was detected (upside pictures) and 20 days after (down side pictures). A and B) Accumulibacter (red) and Tetrasphaera (blue); C) and D) Competibacter (blue) and Defluvicoccus (red); E) and F) *M. parvicella* (red). Total bacteria are shown in green.





- **Bulking** correlates with **poor phosphate removal** (highlighted in red)
- **High abundance** of *Thiothrix* filamentous bacteria
- **Sulfate reduction** during the anaerobic phase (about 30% of influent sulfate)
- **Sulfate reducers** outcompeted **PAOs** by **competing for influent COD**
- **Sulfate reducers** were **outcompeted** by **reducing the anaerobic phase length** (highlighted in green)

Continuous flow system:



- Filamentous **bulking** occurred at **SRT 8 days**
- **Bulking** corresponded with **poor phosphorus removal** and high *Thiothrix* abundance (Sulfate reduction correlated with **SVI** and **P-removal**)
- **Action taken**: The **anaerobic HRT** was **reduced** to phase out the SBRs:
 - Significant reduction in SVI;
 - Significant reduction in sulfate reduction;
 - P-removal, however, was not recovered



4. CONCLUSIONS

- Low SRT EBPR systems are **sensitive** to bulking due to *Thiothrix* and *M. parvicella*
 - **SBR** is **more robust** due to imposed substrate gradients
- **Sulfate reducers** **compete** with **PAOs** for **volatile fatty acids** (via completed or uncompleted oxidation)
- **Sulfate reducers** can be controlled by manipulating the **anaerobic HRT**

ACKNOWLEDGEMENT



The research was financially supported by the Danish Council for Strategic Research, as part of the **Integrated Water Technology** (InWaTech) project, a collaboration between the Technical University of Denmark (DTU) and the Korea Advanced Institute of Science and Technology (KAIST).

References:

- [1] Jimenez, J., Miller, M., Bott, C., Murthy, S., De Clippeleir, H., and Wett, B., 2015. Water Research, *In press*
- [2] Valverde-Pérez, B., Ramin, E., Smets, B.F., and Plósz, B. Gy., 2015. Water Research, 68, 821-830
- [3] Ge, H., Batstone, D.J., and Keller, J., 2015. Water Research, 68, 173-182
- [4] Fang, L.L., Valverde-Pérez, B., Damgaard, A., Plósz, B.Gy., and Rygaard, M., 2015. Water Research, *Accepted with revision*